

Product name	2LV				ES	3L	3L 120
Product code	UP-2LV-22	UP-2LV-29	UPMOD-2LV-22	UPMOD-2LV-29	UP-ES	UP-3L	UPMOD-3L
<b>SPECIFICATIONS</b>							
Height range	21.6"-47.9"						
Width range	41.3"-72.8"		N/A		40.9"-68.5"	Main frame: 46"-77" Extension leg: 42"-72"	24" Depth: 36"-54" 30" Depth: 36"-42"
Depth of foot	21.65"	29.5"	21.65"	29.5"	23.6"	21.65"	
Depth of bracket	19.7"			21.65"			
Assembly time*	15-25 min				10-15 min	20-30 min	
Travel speed	1.6" per second						
Sound level	39 dB						
Weight capacity	260 lbs		220 lbs			420 lbs	400 lbs
Motors	2 (1 per leg)					3 (1 per leg)	
Max operational power draw	180W					280W	
Standby power draw	<0.1W						
Tabletop size range	22"d x 44"w 28"d x 84"w	29"d x 44"w 36"d x 84"w	22"d x 30"w 28"d x 47"w	29"d x 30"w 36"d x 47"w	24"d x 42"w 30"d x 72"w	Main frame: 48"-96" Extension leg: 42"-96"	24" Depth: 36"-54" 30" Depth: 36"-42"
Power cord length	118"						
<b>FEATURES</b>							
Frame finish options	Silver, black, white						
Built-in gyro-sensor anti-collision system	Yes						
Adjustable sensitivity for anti-collision system	Yes						
Casters available	No	Yes				No	
Digital height adjustment handset	Digital display – 4 presets						
Settable min/max heights	Yes						
One touch adjustment to presets	Yes						
Parallel connectivity	Yes				No	Yes	
Changeable inch or cm height display	Yes						
Certifications	UL 962   CSA22.2 No. 68   BIFMA G1   BIFMA X5.5   BIFMA e3 Level 2   GREENGUARD Gold® <b>UP-ES:</b> CSA/UL Listed   BIFMA G1   BIFMA X5.5   BIFMA e3 Level 2   GREENGUARD Gold®						

\* Frame assembly only – does not include table top attachment. Tabletop attachment adds 5-10 min.